


JELIA Series

DELTA Series

- High & Consistent Output
- Pneumatically Operated
- Automatic Insertion, Cutting & Fitting of Loop Handle
- Microprocessor Controlled with Digital Display
- Programmable for Auto Cycle Mode
- Batch Count & Total Count
- Friction Brake on Roll Unwind
- Suitable for Side Seal & Bottom Seal Bag



Types of Bags Possible:



Side Seal-Soft Loop



Bottom Seal-Soft Loop

Features:

DELTA Series

- High & Consistent Output
- Pneumatically Operated
- Automatic Insertion, Cutting & Fitting of Loop Handle
- Microprocessor Controlled with Digital Display
- Programmable for Auto Cycle Mode
- Batch Count & Total Count
- Friction Brake on Roll Unwind
- Suitable for Side Seal & Bottom Seal Bag

Specifications

Model	Bag Width (mm)	Bag Length (mm)	Thickness	Max. Speed*	Connected	Weight	Dimensions
	min. max.	min. max.	of Bag (Micron)	Bags/min	Load KW	Kg	W x L x H cm
SM 600	250-600	250-700	50-90	15~20	1.5	400	178 x 182 x 126

Standard Supply Voltage: 415 V, 3 Phase & Neutral, 50 Hz (Can be changed as per customers requirement)
*Max. speed depends on operator skill & Material Specification

Loop Handle Film Specs. :

- Size = 360mm width
- Thickness = 140-160 Micron
- Pre-Slited Tubular Rolls, Corona Treated on Non Sealing Side

Comp. Air Requirement : 5 Cfm

The manufacturer reserves the right to change design/specifications because of continuous developments.

Accessories/Attachments shown on the photograph may not be part of the standard machine.

Max. Speed shown above is only indicative and the actual speed will depend on size, thickness and the materials of the film. Compressed Air & Chilled Water, If Required, Not in our Scope of Supply.



Œ



303/2 Makarpura Ind. Estate, Vadodara 390 010, INDIA

Tel: + 91-265-2638125, 2638026 • Fax: + 91-265-2638661

E-mail: info@xlplastics.com Website: www.xlplastics.com