

#### **DELTA Series Servo Driven**

- Unwind stand with magnetic particle brake
- Web aligner (EPC) on the unwind
- Tension control with display
- Zipper attachment, friction type with continuous sealing & cooling jaw with water circulation
- Photocell control to convert printed rolls
- Ultrasonic zip crushing attachment
- Servo motor & drive for indexing

# Side seal Zipper



SSZ 800 DELTA

**Models: SSZ 600 DELTA SSZ 800 DELTA** SSZ 1000 DELTA

Suitable for LDPE Film







## Features:

#### **DELTA Series Servo Driven**

- Unwind stand with magnetic particle brake
- Web aligner (EPC) on the unwind
- Tension control with display
- Zipper attachment, friction type with continuous sealing & cooling jaw with water circulation
- Photocell control to convert printed rolls
- Ultrasonic zip crushing attachment
- Servo motor & drive for indexing

### **Optional Attachments:**

- Hole punching device
- Auto stacker
- Handle punch
- Sheet folding device

#### **Specifications**

|  | Model    | Max.Web  | Draw Length mm |      | Max. Speed  | Connected | Film Thickness - Micron |      | Dimensions      |
|--|----------|----------|----------------|------|-------------|-----------|-------------------------|------|-----------------|
|  |          | Width mm | Min.           | Max. | strokes/min | Load KW   | Min.                    | Max. | W x L x H cm    |
|  | SSZ 600  | 600      | 80             | 600  | 40 - 100    | 9 kw      | 50                      | 100  | 130 x 550 x 200 |
|  | SSZ 800  | 800      | 80             | 800  | 40 - 100    | 10 kw     | 50                      | 100  | 150 x 550 x 200 |
|  | SSZ 1000 | 1000     | 80             | 1000 | 40 - 100    | 11 kw     | 50                      | 100  | 170 x 550 x 200 |

Standard Supply Voltage: 415 V, 3 Phase & Neutral, 50 Hz (Can be changed as per customers requirement)

Comp. Air Requirement : 10 Cfm

The manufacturer reserves the right to change design/specifications because of continuous developments.

Accessories/Attachments shown on the photograph may not be part of the standard machine.

Max. Speed shown above is only indicative and the actual speed will depend on size, thickness and the materials of the film.

Compressed Air & Chilled Water, If Required, Not in our Scope of Supply.



(



# **XL Plastics**

Survey No.442-452, NH No. 8, Behind Galaxy Hotel, Por, Vadodara – 391 243.

Tel: + 91-265-2830176, 2830177, 2830178

E-mail : info@xlplastics.com Website : www.xlplastics.com